

2014 Collection

TURBO



Product Information

	Norm	Symbol	
Usage classification	EN 685		21
Wear layer	EN 429		0,15 mm
Total thickness	EN 428		2,30 mm
Standard width	EN 430		1365 gr/m ²
Standard length	EN 426		15 - 30 m

Technical Information

	Norm	Symbol	
Light stability	EN ISO 105 B02		≥ 6 - 7
Dimensional Stability	EN 434		≤ 0,40 %
Underfloor heating	ISO 8302		Suitable
Residual Indentation	EN 433		≤ 0,35 mm
Impact Sound Insulation	EN ISO 140-8		13 dB
Reaction to fire	EN 13501-1		B _{fl} /S1
Slip resistance	DIN 51130		R10

2014 Collection

TURBO



Product Information

	Norm	Symbol	
Usage classification	EN 685		21
Wear layer	EN 429		0,15 mm
Total thickness	EN 428		2,30 mm
Standard width	EN 430		1365 gr/m ²
Standard length	EN 426		15 - 30 m

Technical Information

	Norm	Symbol	
Light stability	EN ISO 105 B02		≥ 6 - 7
Dimensional Stability	EN 434		≤ 0,40 %
Underfloor heating	ISO 8302		Suitable
Residual Indentation	EN 433		≤ 0,35 mm
Impact Sound Insulation	EN ISO 140-8		13 dB
Reaction to fire	EN 13501-1		B _{fl} /S1
Slip resistance	DIN 51130		R10