

Product Description

- **Dimensions** 1285 L x 186 W x 8 TH
- **Packaging** Box : 8 boards - 1,91 m² (14,5 kg)
Pallet : 56 boxes - 107,08 m² (835 kg)
- **Composition**
 - › Surface layer Direct Laminated Papers. Paper impregnated with melamine resin
 - › Substrate Moisture-resistant High Density Fibreboard, HDF
 - › Backing Direct Laminated Paper. Paper impregnated with melamine resin
- **Features** HydroPlus, Woodstructure+, Matlook
- **Installation** Best Loc : glue-free mechanical locking system produced under license of Välinge Innovation AB, Flooring Industries Ltd and Faus Group Inc
- **Installation instruction** see box inlay or www.berryalloc.com

Requirements

- **General requirements** according to EN13329
- **Classification requirements** class 23/32

Characteristics	Method	Requirement	Typical value
Abrasion resistance	EN13329	AC4 (IP≥4000)	IP≥4000
Impact resistance	EN13329	IC2	IC2
Thickness swelling	EN13329	≤ 18%	≤ 10%
Resistance to staining	EN438	5 (groups 1+2); 4 (group 3)	5 (groups 1+2); 4 (group 3)
Resistance to cigarette burns	EN438	4	4
Effect of a furniture leg	EN424	No damage (foot type 0)	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage	No change in appearance or damage

CE - classification according to EN14041

- **Fire resistance** C_{fl}-S1
- **Formaldehyde** E1
- **Slipperiness** DS

Other technical data

- **Sustainability of forests** : PEFC certified
- **Labelling according to French VOC emission regulation** : A+
- **CARB** : Phase II compliant
- **Floor heating** : see specific instructions at www.berryalloc.com
- **Thermal resistance in combination with underlay Excellence Endurance** : 0,10 m² K/W

Warranty and maintenance

- **Residential warranty** Lifetime
- **Commercial warranty** 5 years
- **Warranty conditions** see www.berryalloc.com
- **Care and maintenance** see www.berryalloc.com

