

**Product Description**

- **Dimensions** 1281 L x 321 W x 8 TH 605 L x 282 W x 8 TH
- **Packaging** Box : 5 boards - 2,06 m<sup>2</sup> (15,5 kg) 12 boards - 2,05 m<sup>2</sup> (15,2 kg)  
Pallet : 63 boxes - 129,53 m<sup>2</sup> (1001 kg) 32 boxes - 65,51 m<sup>2</sup> (501 kg))
- **Composition**
  - > Surface layer Direct Laminated Papers. Paper impregnated with melamine resin
  - > Substrate Moisture-resistant High Density Fibreboard, HDF
  - > Backing Direct Laminated Paper. Paper impregnated with melamine resin
- **Features** Microbevel, Stonestructure, Stonestructure+
- **Installation** Best Loc X-treme : glue-free mechanical locking system with a short side droploc produced under license of Välinge Innovation AB, Flooring Industries Ltd and Faus Group Inc
- **Installation instruction** see box inlay or [www.berryalloc.com](http://www.berryalloc.com)

**Requirements**

- **General requirements** according to EN13329
- **Classification requirements** class 23/32

Characteristics	Method	Requirement	Typical value
Abrasion resistance	EN13329	AC4 (IP ≥ 4000)	IP ≥ 4000
Impact resistance	EN13329	IC2	IC2
Thickness swelling	EN13329	≤ 18%	≤ 10%
Resistance to staining	EN438	5 (groups 1+2); 4 (group 3)	5 (groups 1+2); 4 (group 3)
Resistance to cigarette burns	EN438	4	4
Effect of a furniture leg	EN424	No damage (foot type 0)	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage	No change in appearance or damage

**CE - classification according to EN14041**

- **Fire resistance** C<sub>fl</sub>-S1
- **Formaldehyde** E1
- **Slipperiness** DS

**Other technical data**

- **Sustainability of forests** : PEFC certified
- **Labelling according to French VOC emission regulation** : A+
- **CARB** : Phase II compliant
- **Floor heating** : see specific instructions at [www.berryalloc.com](http://www.berryalloc.com)
- **Thermal resistance in combination with underlay Excellence Endurance** : 0,10 m<sup>2</sup> K/W

**Warranty and maintenance**

- **Residential warranty** Lifetime
- **Commercial warranty** 5 years
- **Warranty conditions** see [www.berryalloc.com](http://www.berryalloc.com)
- **Care and maintenance** see [www.berryalloc.com](http://www.berryalloc.com)

