


**Product Description**

- **Dimensions** Size plank 1213 L x 171 W x 5 TH (mm)
- **Packaging** 8 planks per box = 1,66 m<sup>2</sup>  
Weight approx. 16 kg  
55 boxes / pallet = 91,34 m<sup>2</sup> (900 kg)
- **Composition** 1. UV layer / PU coating  
2. 0,55 mm wear layer  
3. Print film  
4. Multilayer based on virgin PVC
- **Features** Micro V bevel on 4 sides
- **Installation** Glue-less mechanical locking system
- **Installation** see box / [www.berryalloc.com](http://www.berryalloc.com)

- **Dimensions** Size tile 603 L x 298 W x 5 TH (mm)
- **Packaging** 8 tiles per box = 1,44 m<sup>2</sup>  
Weight approx. 14 kg  
60 boxes / pallet = 86,31 m<sup>2</sup> (860 kg)

**Tile and plank construction:**



**Requirements**

Classification Requirements class 23/33/42

Characteristics	Method	Unit	Typical value
Thickness	EN 428	mm/ inch	5 /20
Wearlayer	EN 429	mm/MIL	0,55 / 22
Classification	EN 685	class	23/33/42
Fire Classification	EN 13501 - 1	class	B <sub>fl</sub> -s1
Slipresistance	DIN 51130	class	R9
	EN13893	class	DS
Weargroup	EN 660 - 1		T
Residual Indentation	EN 433	mm	<0,1
Thermal Resistance	DIN 52612	m <sup>2</sup> K/W	0, 02
Castor Chair	EN 425		No changes in appearance or damage
Colourfastness	ISO 105-B02	Grade	> 6 Grade
Chemical product resistance	EN 423		OK
Floor heating system		°C	Yes, max. 27
Dimensional stability	EN 434		<0,25%
Formaldehyde Emission	EN 717-1		E1



**Warranty and maintenance**

- Residential warranty: Lifetime / Commercial warranty: 10 years
- Warranty conditions, care and maintenance: see [www.berryalloc.com](http://www.berryalloc.com)

09/2012

